



8" Dual Cone In-Ceiling Speaker with 25V/70V 5-Watt Transformer and 62-8 Baffle

SD72W

SKU: 25082 UPC: 612079179954

The loudspeaker used in the SD72W is the next generation of Atlas high performance cone loudspeakers very similar to the preceding C-Series loudspeakers. The similarity in the sonic qualities ensures that contractors and designers who have worked with the AtlasIED C-Series in the past will know exactly what to expect when they use the SD72W.

Model SD72W is a dual cone 25-watt 8" (205mm) loudspeaker with a 10oz. (260g) ceramic magnet. It includes a curvilinear treated paper cone for lower harmonic distortion. The loudspeaker is also equipped with a full 1" diameter copper voice coil with a black anodized aluminum former for better power dissipation. Package includes factory installed 25/70.7V line matching transformer with tap selections ranging from .25 to 5 watts.

Model SD72W operates within a frequency response range of 45Hz - 19kHz (nominal) with a sensitivity of 97dB and a dispersion angle of 105 degree .

The SD72W includes a factory installed CRS baffle with concealed loudspeaker mounting studs and includes screw mount hardware. The SD72W baffle features standard mounting holes to accommodate the majority of AtlasIED 8" tile bridges mounting rings and enclosures. When specifying mounting hardware be advised that the dimensions of the SD72W baffle match the AtlasIED Model 62-8. The baffle finish is white powder coat epoxy.

Features:

- 10oz Dual Cone Speaker Provides Familiar Response & Performance
- Attractive CRS White Powder Coat Baffle
- Individually Packaged for Stocking & Ordering Convenience
- Quality 5 Watt-Dual Voltage Transformer
- ETL Certified Safety Listed to UL1480 and UL2043.

Speaker Type	8" Treated Paper
Sensitivity	97dB Average
Power Taps	.25, .5, 1, 2, & 5 Watts
Frequency Response	55Hz - 8kHz
Dispersion	105° (2kHz Octave Band, -6dB Points)
Diameter	8 1/8" (20.6375 cm)
Safety Listed	1480