



Maestro LED+ Dimmer - Stone

MACL-153M-ST

SKU: 62474 UPC: 784276010771

Maestro LED+ Dimmer

Dimmer for dimmable LED and CFL bulbs

Features

- Large tapswitch with a rocker-style dimmer for a standard designer wallplate opening.
- Advanced dimming technology designed for compatibility with a broader range of high efficacy bulbs.
- UL Listed to control:
 - Dimmable LEDs
 - Dimmable compact fluorescent lamps (CFLs) with integrated ballast
 - Lutron LTEA Hi-lume 1% forward-phase LED driver
 - Halogen
 - Incandescent
- Low-end adjustment to accommodate a wide range of bulbs.
- No neutral required for retrofit applications.
- Tapswitch returns load to previous level.
- Can be used in single-pole, multi-location (using MA-R), or 3-way mechanical switch1 applications.
- Coordinating Claro and stainless steel wallplates available separately.
- 100% factory tested.
- NEMA SSL-7A Compliant.
- Formerly CL.

Model Number:

- MACL-153M-XX Single-pole/3-way1 / Multi-location
- MACL-153MH-XX-C Single-pole/3-way1 / Multi-location

Packages:

- MACL-153M-RHW-XX includes: 1 MACL-153M-XX, 1 MA-R-XX, and 2 CW-1-XX.
- MACL-153MRHW-XXC includes: 1 MACL-153M-XX, 1 MA-R-XX, and 2 CW-1-XX.

Sub Brand: Maestro Application: Lighting Control Type: Digital fade dimmer, multi-location/3-way/single-pole Color: Mounting: Wallbox Voltage Rating: 120 VAC Wattage: 600 W Actuator: Tapswitch Connection: Screw terminals Gang: Frequency Rating: 50/60 Hz Standard: UL CSA NOM Operating Temperature: 0 to 40 degrees Celsius Special Features: Controls dimmable 150 W LED/CFL (screw-base) or 600 W incandescent/halogen loads. Provides true dimming from each location (with companion dimmers). Provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents.