



## 2-Channel 150-Watt Slim 1U Power Amplifier

AMP150/2

SKU: 64093    UPC: 81993201234

Introducing the Elura AMP150/2 2-Channel 150-Watt Amplifier, the powerhouse that takes your audio experience to the next level. Designed with precision and engineered for performance, this slim 1U power amplifier delivers exceptional sound quality and versatility in a compact form factor.

The Elura AMP150/2 is packed with power, boasting two channels of 150 watts each, for a total power output of 300 watts. Whether you're driving a pair of speakers or bridging the channels to power a subwoofer, this amplifier ensures robust and dynamic audio reproduction. Experience the full range of frequencies with clarity, precision, and a punch that will leave you amazed.

The AMP150/2 is built with high-quality components and advanced circuitry, ensuring reliable and efficient operation. It features a robust power supply and advanced protection circuitry to safeguard against overheating, short circuits, and other potential issues, providing peace of mind and ensuring the longevity of your investment.

### Features

- 2 Channel Amplifier
- Digital high power amplification
- Power Output
  - 150 Watts per Channel @ 4 ohms
  - Bridged 300 Watts @ 8 ohms
- Low Impedance Design
- Bridgeable
- Low Noise
- Automation circuit
- Small chassis
- Less Heat
- Efficient design
- Rack mountable

**2-YEAR WARRANTY** - Elura speaker products are guaranteed to meet or exceed the specifications included in this manual and carry with them a 2-year limited warranty under normal conditions of use. This warranty covers free parts and labor on all components with the obligation that Elura will repair or replace any component found defective in materials or workmanship. This warranty does not apply to products that have been abused, incorrectly installed, modified, disassembled and/or repaired by anyone other than Elura or our appointed repair facility.

<b>Number of Channels</b>	2
<b>Power Output</b>	150 Watts @ 4 ohms 300 Watts @ 8 ohms (Bridged)
<b>Inputs</b>	1 x Stereo RCA

<b>Outputs</b>	1 x Stereo RCA 2 x Speaker 5-way Binding Post
<b>THD+N</b>	@4?=0.9%/ @8ohm=1.0%
<b>Input Sensitivity</b>	600mV
<b>Frequency Response</b>	10Hz - 20kHz
<b>High Pass Filter</b>	150Hz - 20kHz /-3dB
<b>Low Pass Filter</b>	10Hz - 150Hz / -3dB
<b>Signal to Noise Ratio</b>	-75dB
<b>Auto Turn Off Time</b>	8 min
<b>Auto Turn ON</b>	5mV
<b>Trigger</b>	12 Volts In/Out
<b>Supply Voltage</b>	AC230V / 50HzAC115V / 60Hz
<b>Rack Unit</b>	1U Chassis
<b>Product dimensions</b>	With Rack Ears: W 19.00 x H 2.15 x D 10.72" Without Rack Ears: W 16.85" x H 2.15" x D 10.72"