



## 18/4 Stranded Speaker / Security Cable CMR 500' Box - White

18/4-WT-500

SKU: 54787

4C/18 AWG BC 16 STRAND, SECURITY/COMMERCIAL AUDIO CABLE, UL CMR, PVC JKT- WHITE- 500 BOX

### Applications:

Security Systems, Intercom Systems, Sound/Audio Systems, Power-Limited Controls. Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

### Features:

- Multi-Conductor unshielded insulated stranded bare copper conductors, twisted with a sunlight resistant PVC jacket. Ripcord and sequential foot markings printed on jacket.
- CMR/FPLR/CL2R/CL3R/CMG/FT4
- 22-16 AWG: NEC FPLR/760, CMR/800, CL3, CL2R/725
- 14-12 AWG: FPLR, CL3R
- ETL, c(ETL), RoHS, CE

<b>Construction Characteristics:</b>	
<b>Conductor:</b>	
Material	Stranded Bare Copper
Size	18AWG X 2C
Construction	16/0.25+/-0.004mm
<b>Insulation:</b>	
Material	PVC
Min. Thickness	0.24mm
AVG. Thickness	0.26mm
Diameter	1.70+/-0.05mm
Colors	Black & Red & White & Green
<b>Jacket:</b>	
Material	PVC
Min. Thickness	0.45mm
AVG. Thickness	0.50mm
Diameter	5.10+/-0.10mm
Rip Cord	Nylon
Color	Gray or White
<b>Electrical &amp; Physical Characteristics:</b>	
Operating Temperature Range	- 20°C + 75°C
Conductor Resistance	Max 22.8ohm/km at 20°C
Insulation Resistance	Min 50M $\Omega$ *km at 20°C
Capacitance	80+30 pf/m
Dielectric Strength	Min AC1.5KV

Rated Voltage	Max 80Volts
<b>Packaging:</b>	
Approx Weight	7.85kgs/17.27bs 15.0kgs/33.0bs
Approx Dimension (mm)	280X260X280 350X260X350
Package	500ft/Box 1000ft/Box
Packages per pallet	64 36