



4K 18G 2x1 40M HDBaseT PoH Wallplate Switcher (Tx)

KD-X2X1WDTX

SKU: 174759 UPC: 815996021225

- **Aluminum Decora plate** (qty 1)
- **Decora mounting screws with flat head** (qty 4)
- **Gang-box mounting screws** (qty 4)
- **Mounting bracket** (qty 2)
- **3-pin phoenix terminal** (qty 1)
- **2-pin phoenix terminal** (qty 1)

Technical: KD-X2x1WDTx Inputs: 1 HDMI, 1 Display Port, 1 IR Sensor, 1 Serial IR KD-X2x1WVTx Inputs: 1 HDMI, 1 DB15, 1 3.5mm Stereo Audio, 1 IR Sensor, 1 Serial IR Outputs: 1 CAT5e/6 UTP/STP, 1 Bi-Directional RS-232 DDC Signal (Data): Input DDC Signal: 5 Volts p-p (TTL) HDMI Video/Audio Signal: Input Video Signal: 1.2 Volts p-p KD-X2x1WVTx VGA Video Signal: Input Video Signal: 1.2 Volts p-p KD-X2x1WVTx Analog Audio Input: 2 VRMS line audio, 3.5mm Stereo Female KD-X2x1WDTX Display Port Video/Audio Signal: Input Video Signal: 1.2 Volts p-p HDMI Connector: Type A, 19 Pin Female KD-X2x1WVTx VGA Connector: 15 Pin, Female KD-X2x1WDTx Display Port Connector: Full Size, 20 Pin Female RJ45 Connector: Shielded Link Connector, HDBaseT IR Connectors: 1 IR Sensor, 1 2-pin phoenix terminal RS-232 Connector: 3-pin phoenix terminal General: Regulation: CE, RoHS, WEEE, EAC Enclosure: Tx unit: Brushed aluminum face with black metal backing Dimensions: 3.21 x 2.06 x 0.787 (Wall-plate) Product Weight: 0.7 lbs Packaging: 10.6 x 5.9 x 2.1 (270x150x55mm) Packaging Weight: 1.3 lbs