



Replacement Bezel Assembly for KX2 - Brush Aluminum

PBZBR-KX2

SKU: 47221

Cover for KX2 - brushed aluminum Number: 28PBZBR-KX2 Type: PBZBR-KX2

Power	+9VDC to +16VDC, 1A max
Power Management	Adjustable backlight brightness, Ambient light sensor, Proximity sensor
Touchscreen Display	High-brightness color TFT LCD QVGA (240w x 320h pixels) with 65K colors Integrated high-resolution resistive touchscreen
Display Size	2.8" (71mm) diagonal
Display Backlight	LED Backlit, 200nit
Infrared Output	Through control port, 200mA output Drives up to 1000 ft (300 m) of wire
Ethernet Port	10/100 Base-T with Power-over-Ethernet
Audio	Beeper
Total System Memory	32MBytes Flash (non-volatile) memory
Device Capability	Total number of devices is limited only by memory
Macro Capability	Unlimited steps in a single macro Total number of macros is limited only by memory Macro capability on every button
Communications	USB programming port
Enclosure	High-impact molded ABS plastic
Mounting	Integrated mounting wings, or screws through front bezel
Front Plate Dimensions (H x W)	4.4 in (112mm) x 4.6 in (117mm)
Installation Cut-Out (H x W)	3.789" in (96.5mm) x 3.789" in (96.5mm)
Total Depth in Wall	1.2 in (31mm) Plus cables
Operating Temperature	+32°F to +122°F (0°C to +50°C)
Operating Humidity	5% to 95% Non-condensing
Weight	7.5 oz (212g)
Warranty	Three Years (Parts & Labor)