



FX2 On-Wall Speaker

EMFX2

SKU: 155807 UPC: 877929006204

The EM-FX2 features dual Folded Motion XT tweeters in a wide-dispersion array ideally suited for surround channel applications. A single 6.5-inch doped fiber-cone woofer provides powerful low-frequency extension. Available in a black satin finish, the EM-FX2 is designed to corner mount, wall mount or angle-wall mount for versatile surround sound placement in any room.

Frequency Response	55-25,000 Hz \pm 3dB
Recommended Amplifier Power	20-200 watts per channel
Horizontal Dispersion	160°
Vertical Dispersion	30°
Sensitivity	93 dB @ 2.83 volts/ meter
Impedance	5 Ohms Compatible with 4, 6, or 8 Ohm rated amplifiers.
Crossover Frequency	2,300Hz
High Frequency Transducer	Two 1.25" x 2.4" (3.2cm x 6.1cm) Folded Motion XT Transducers with 4.5" x 2.75" (11.4cm x 7cm) diaphragm
Low Frequency Transducer	6.5" (16.5cm) paper cone with cast aluminum basket. Ported.
Components	Custom air core coil inductors. Polyester film capacitors in series and low DF electrolytic capacitors in parallel. Tweeter thermal/current protection.
Inputs	Push style with banana jacks
Weight	16 lbs. (7.3 kg)

Dimensions	14.9" x 14" x 6.8 " (37.9cm x 35.5cm x 17.2cm)
------------	--