



## XT Series CI 5.25" LCR In-Wall Speaker

XTW5-LCR

SKU: 169784    UPC: 810123025534

The smaller of the two "LCR" models in the Motion XT CI series, the XTW5-LCR functions equally well as a center, front or surround channel, or anywhere higher performance and/or a more rectangular shape is desired. A perfect complement for a flat panel TV or projector screen; the XTW5-LCR allows for flexible placement and incredible performance. Its FMT XT tweeter can be rotated to help create the sound dispersion that works best for your space.

Frequency Response	61 - 25,000 Hz $\pm$ 3dB
Tweeter Dispersion (horizontal x vertical)	80 x 30 degrees
Recommended Amplifier Power	Range 50-250 Watts
Sensitivity	92dB @2.83V/ 1 meter
Impedance	4 ohms. Compatible with 8 ohms
Crossover Frequency	2,180 Hz
High Frequency Driver	FMT Transducer 1.27"x 2.4"(3.22cm x 6.09cm) Opening 4.5"x 2.75"(11.43cm x 6.98cm) Diaphragm
Crossover Type	2 way
Driver Configuration	1 x 1.27"x 2.75"FMT, 2 x 5.25"Woofers
Woofer Specifications	Two 5.25"(13.33 cm) cast aluminum basket, black Kevlar with Nomex backer cone, Open back chamber format. Concave dust cap.
Cabinet Material	Black w/ White Paintable Grill
Connector	Push style

Components	Custom air core coil inductors, polyester film capacitors in series and low DF electrolytic capacitors FMT thermal/current protection.
Max Power Handling	125 Watts
Weight	4.4 lbs. (2 kg) each
Dimensions (overall size)	7.87"x 15.79"x 3.32"(20 x 40.1 x 8.43cm)
Required Wall Opening (includes tolerance)	14.5"x 6.5"(36.8 x 16.5cm)
Projection From Wall Surface	0.12"(0.3cm)
Depth Behind Wall Surface	3.20"(8.13cm)