



PoE Injector, 15VDC, 12W- Black

POE-15-12W

SKU: 170990    UPC: 810354021176

Ubiquiti Networks offers Power over Ethernet (PoE) Adapters to power a variety of Ubiquiti products. The PoE Adapters are compatible with most Ubiquiti PoE devices. Ubiquiti PoE Adapters provide a variety of features to help protect your PoE devices:

- Surge protection
- Clamping protection
- Maximum surge discharge
- Peak pulse current
- AC cable with earth ground

Dimensions	85 x 44 x 29 mm (3.35 x 1.73 x 1.14")
Weight	91.7 g (3.24 oz)
Output Voltage	15VDC @ 0.8A
LAN Activity Indicator	No
Gigabit LAN Port	No
Remote Reset Capability	No
Reset Button	No
Rated Voltage	100-240VAC @ 50/60Hz
Input Current	0.3A @ 120VAC, 0.2A @ 240VAC
Inrush Current	<30A Peak @ 120VAC, <60A Peak @ 230VAC
Efficiency	75+%
Output Ripple	1% Max.
Switching Frequency	50 kHz
Line Regulation	? 3%
Load Regulation	? 5%
2-Pair Powering	Pins 4, 5 (+) and Pins 7, 8 (-)
4-Pair Powering	-
Operating Temperature	0 to 40° C (32 to 104° F)
Storage Temperature	-30 to 70°C (-22 to 158° F)
Operating Humidity	35 to 95% Noncondensing
AC Connector	IEC-320 C6
Data IN / POE	RJ45 Shielded Socket
Surge Protection	Difference and Common Mode
Clamping Protection	11V Data, 60V Power
Max. Surge Discharge	1500A (8/20 ?s) Power
Peak Pulse Current	36A (10/1000 ?s) Data
Shunt Capacitance	<5 pF data
Response Time	<1 ns
Certifications	CE, FCC, IC, UL