



18/4 Stranded Shielded PVC 500' Box - Gray

18/4SH-GY-500

SKU: 43310 UPC: 810070010775

4C/18 AWG STRANDED SHIELDED- GRAY- 500 FT BOX

Applications:

Security Systems, Intercom Systems, Sound/Audio Systems, Power-Limited Controls. Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Features:

- Multi-Conductor shielded insulated stranded bare copper conductors, twisted with overall AL mylar shielding (with drain) and sunlight resistant PVC jacket. Ripcord and sequential foot markings printed on jacket.
- CMR/FPLR/CL2R/CL3R/CMG/FT4
- 22-16 AWG: NEC FPLR/760, CMR/800, CL3, CL2R/725
- 14-12 AWG: FPLR, CL3R
- ETL, c(ETL), RoHS, CE

Conductor	18 AWG 16 Strand SBC Cond.
Total Cable Weight	54 kg/km
Insulation	PVC
Shield	Foil Shield 0.75
Drain	24 AWG 7 Strand STC Cond.
DC Resistance 25°C	6.5 Ohms / 1000 ft
Impedance	53.7 Ohms
Velocity of Prop	0.64
Final Diameter	0.196 inches
Jacket	PVC
Mutual Capacitance	45.9 pF/ft
Inductance.	1.3 mH/km
Cabled OD Avg	0.19
Ins Thickness	0.01
Jkt Thickness	0.015
Certified	UL CL3R / UL C(UL) CMR
Flame Rating	Riser
Max Voltage	300V