



8" Premium In-Wall LoudSpeakers

CONTROL-128W

SKU: 102406 UPC: 50036905008

The Control 128W is a premium in-wall speaker within the JBL Professional Control® Contractor line designed for applications such as foreground music, boardrooms, reception areas, airports, convention centers, cruise ships, retail outlets, restaurants, museums, surround locations, or any critical listening application where top performance from a loudspeaker with minimal visual impact is required.

Features:

- 200 mm (8 in) polymer-coated aluminum-cone woofer with pure butyl rubber surround.
- 25 mm (1 in) pure-titanium dome low-diffraction swivel aimable titanium tweeter.
- High-slope crossover for natural midrange sound.
- Extended bandwidth performance of 30 Hz – 20 kHz.
- 60 W continuous (120 W program, 240 W peak)
- Power handling (128 W).

Frequency Range	38 Hz - 20 kHz (-10 dB)
Power Rating	200 W Peak 100 W Continuous Program Power 50W Continuous Pink Noise
Sensitivity	90 dB SPL
Coverage Angle	180°H x 160°V
Impedance	8 ohms
Drivers	LF: 200 mm (8 in) polymer-coated aluminum cone, pure butyl rubber surround. HF: 25 mm (1 in) pure-titanium dome with cloth suspension on low-diffraction swivel-mount with -10 degree aimability
Input Connectors	Screw-down Euroblock-type connector. Max wire size 14 AWG (1.5 mm) ²
Crossover Network	2nd order Low Pass to the woofer and 2nd order High Pass to the tweeter.
Optimum Air Cavity Behind Speaker	40 to 80 liters (1.4 to 2.8 cu ft)
Outside Dimensions (H x W x D)	334 x 257 x 110 mm (13.1 x 10.1 x 4.3 in), 102 mm (4.0 in) front of wall to back of speaker.
Maximum Wall Thickness	32 mm (1.25 in)
Cutout Size (H x W)	300 x 225 mm (11.9 x 8.9 in), Cutout template included.
Net Weight (each)	2.6 kg (5.5 lb)
Shipping Weight (ea)	128 W: 5.9 kg (13.0 lb)
Included Accessories	Cutout template & paint shield