



resideo

ProSeries Wireless Door / Window Sensor

PROSIXCT

SKU: 170124 UPC: 194160000076

Designed for systems that support SiX Two-Way Wireless Technology, these devices deliver significant advantages—including faster installation, easier troubleshooting, remote diagnostics and increased RMR. The suite of next-generation devices includes motion, smoke, CO, heat and glassbreak detectors, door/window sensors, two-way wireless key and siren.

Features

- SiX sensors feature a battery pull-tab, auto-enrollment and no-touch adjust to speed installation and eliminate errors
- Devices can be configured remotely as needed, reducing the need to schedule on-site visits
- The System Health Check feature lets you monitor device signal strength, sensor settings, and battery life anytime, anywhere via AlarmNet 360, letting you quickly and proactively troubleshoot
- SiX Two-Way Wireless Technology employs true, 128-bit AES encryption for a high level of security
- Reduce truck rolls with user-replaceable batteries and the ability to remotely adjust sensor parameters and download software updates

PROSIXCT PROSERIES DOOR/WINDOW SENSOR Power Supply Battery Powered For Use With ProSeries Control Panels WiFi Yes Tamperproof Yes Application Security System Sensors Includes Mounting hardware Product Height 1.4 in, 27.9 mm Product Length 3.1 in, 78.7 mm Product Width 1.6 in, 40.6 mm Color White Ambient Relative Humidity (Max) 95%, Non-Condensing Battery Size Panasonic CR123A, Duracell DL123A, Huiderrui CR123A, 3 V Battery Type Lithium Number of Batteries 1 Ambient Operating Temperature (Max) 122 °F, 50 °C Ambient Operating Temperature (Min) 32 °F, 0 °C Mounting Location Surface Mount