



14/2 Stranded Plenum Security Alarm Cable 1000' Spool - White

14/2P

SKU: 23216 UPC: 810070014926

2C/14 AWG STRANDED PLENUM Security Alarm Cable WHITE - 1000 FT SPOOL

Applications:

Security Systems, Intercom Systems, Sound/Audio Systems, Power-Limited Controls. Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Features:

- Multi-Conductor unshielded low smoke PVC insulated stranded bare copper conductors, twisted with overall low smoke PVC jacket. Ripcord and sequential foot markings printed on jacket.
- CMP/FT6 Rated, FPLP, CL2P, CL3P
- 22-16 AWG: NEC FPLP/760, CMP/800, CL3P, CL2P/725
- 14-12 AWG: FPLP, CL3P
- ETL, c(ETL), RoHS, CE

| | |
|--|--------------------|
| Conductor | 14 AWG BARE COPPER |
| Conductor Stranding | 19 |
| Nom Cond DC Resistance, ohms/1000 ft | 2.6 |
| Insulating Material Type | PVC Plenum |
| Insulation Wall Thickness, inches | 0.011 |
| Conductor Insulated O.D., inches | 0.097 |
| Final Twisted O.D., inches | 0.193 |
| Jacket Wall Thickness, inches | 0.017 |
| Jacket Material Type | PVC Plenum |
| Finished Cable O.D., inches | 0.230 |
| Total Cable Weight (lb/1000 ft) | 40.3 |
| Voltage Rating (Volts) | 300 |
| Overall Temperature Rating (degrees Celsius) | 75 |
| Nominal Mutual Capacitance, pF/ft | 22 |
| Nominal Impedance (ohms) | 67 |
| RoHS Compliant | Yes |