



4" Background Music Ceiling LoudSpeakers

CONTROL-24C-MICRO

SKU: 102655 UPC: 50036904643

The Control 24C Micro is a compact in-ceiling speaker, providing full, high quality sound for background music and music-plus-paging systems.

Features:

- Extremely wide 150° coverage.
- Smooth frequency response.
- 4.5 in (115 mm) woofer, injection molded graphite cone with butyl rubber surround.
- .5 in (12 mm) polycarbonate tweeter for extended response.
- Control 24C Micro is 8 ohms and handles 15 W.
- Shallow 4 in (100 mm) depth.
- Packaged with grille, backcan and tile rails for fast installation and easy dealer stocking.

Frequency Range	85 Hz - 25 kHz
Power Rating	IEC System Long-Term Ratings (low-Z direct): 30 Watts Continuous Program Power 15 Watts Continuous Pink Noise (60W peak), 100 hrs
Sensitivity	86 dB (100 Hz - 10 kHz)
Crossover Frequency	3.5 kHz
Maximum SPL (1m)	98 dB (104 dB peak)
Coverage Angle	150° conical
Impedance	7.1 ohms
Input Connectors	Screw-down terminals.
Drivers	LF Driver: 115 mm (4.5 in) HF Driver: 12 mm (0.5 in)
Safety Agency	Suitable for use in air handling spaces per UL1480, UL2043, NFPA90 & NFPA 70. S7232/UL Listed, Signaling Speaker. Transformer UL registered per UL1876. In accordance with IEC60849/EN60849.
Backcan	formed steel (included "blind-mount")
Baffle/Rim	Medium impact polystyrene, fire rated UL94V-0
Ceiling Cutout Size	167 mm (6.6 in) diameter (cardboard cutout template included)
Included Accessories	C-shaped support backing plate 2 tile support rails (fits both 2 ft and 600 mm tiles) Cutout template, cardboard
Plenum Usage	Yes, backcan included