



## Sat 60 Landscape Satellite Speaker

ODSAT60

SKU: 155759    UPC: 810123022984

MartinLogan ODSAT60 Outdoor Sat 60 Landscape Satellite Speaker. \*Note: Mounting system is sold separately.

As much as carefully chosen adornments enhance the visual appeal and enjoyment of the scenery, compelling music from high-performance speakers enhances the ambiance. MartinLogan's Outdoor Living system brings unmatched audio quality to the music in your outdoor living space. Rugged, all-weather materials, completely weather- and water-proof construction, and endless mounting and placement options make MartinLogan's Outdoor Living Audio System the best way to expand the reach of your high-performance audio entertainment.

Each individual satellite speaker is a sealed, completely waterproof enclosure, molded in fade-resistant thermoplastic and tinted to blend unobtrusively with your outdoor decor. It features exclusive MartinLogan speaker technology, with premium driver and tweeter components in a single wide-dispersion shell casing. Outdoor Living speakers deliver a dynamic, natural sound unmatched by other outdoor loudspeakers.

### Features

- Built for the Outdoors: Rugged, all-weather materials, completely weather- and water-proof construction, and endless mounting and placement options
- All-Weather Satellite Speakers
- All-Weather Subterranean Subwoofers: The woofer's low-heat design is vented through the "mushroom cap," providing a constant flow of fresh air while always protecting the system from harsh weather and water
- Outdoor Living speakers are scalable
- Quick Connect System: Mount the speakers on the ground, on a deck rail, in a tree, or under an eave Note: mounting system is sold separately
- The scalable Outdoor Living system can be powered using the Crown Amplifier, direct from MartinLogan

Frequency Response	90-20kHz $\pm$ 3dB
Recommended Amplifier Power	20-160 watts per channel
Sensitivity	Room: 92 dB, Anechoic: 88 dB
Impedance	Compatible with 8 ohms Compatible with 4, 6, or 8 Ohm rated amplifiers.
Crossover Frequency	2,500 Hz
High Frequency Transducer	0.75"(1.9cm) aluminum dome, ferro-fluid cooled tweeter
Low Frequency Transducer	6"(15.25cm) mineral filled poly cone

Audio Controls	Input: 8-Ohm, 70 Volt (3.75W, 7.5W, 15W, or 30W), 100 Volt (7.5W, 15W, or 30W)
Inputs	Speaker Wire
Weight	6.5 lbs. (3 kg)
Dimensions without stem	8.3" x 8.3" x 11.3 " (21cm x 21cm x 28.6cm)
Dimensions with stem	12.8" x 8.3" x 11.3" (32.5 cm x 21cm x 28.6cm)