



## MW4-LCR 4" LCR In-Wall Speaker

MW4-LCR

SKU: 169778    UPC: 810123025602

One of the most compact in-wall speakers in MartinLogan history, the MW4-LCR expertly blends high performance and maximum flexibility. The MW4-LCR is a true “Left, Center, Right” speaker that can be used as a front, surround or center channel wherever high quality sound and a small footprint are desired.

### Features

- **The MartinLogan Sound**

Regardless of the environment, our speakers sound better, more articulate, detailed, and realistic. With Controlled Dispersion and one of the clearest tweeters in the industry, our architectural models can compete with and often exceed the performance of traditional speakers.

- **Controlled Dispersion**

Room acoustics are extremely important. Everything in the listening room has an impact on the sound of your speakers, so we try to minimize the harmful effects by focusing the sound directly on your ears. This increases clarity, and detail regardless of the rooms design.

- **Performance Meets Aesthetics**

While there are many choices of CI speakers out there, MartinLogan stands out for bringing unique, high-performance technologies together in a package that perfectly blends discrete sound with noticeable quality. Performance and Aesthetics, both without compromise.

- **Folded Motion Tweeter**

This miracle of audio engineering gives high efficiency and low distortion a new benchmark. Our signature Folded Motion Tweeter uses an extremely lightweight diaphragm, in a space saving “folded” design, to deliver incredible detail, speed, and accuracy in a small space.

- **Fiberglass Woofers**

All Motion CI speakers feature lightweight woven fiberglass cones specifically engineered for their application to blend seamlessly with the lightning speed of our signature Folded Motion Tweeter.

Frequency Response	78 - 25,000 Hz $\pm$ 3dB
Aiming	N/A
Sensitivity	93dB @2.83V/ 1 meter
Impedance	Compatible with 8 ohms
Crossover Frequency	2,800 Hz

High Frequency Driver	FMT Transducer 1"x 1.4"(2.6cm x 3.6cm) Opening 5.25"x 1.75"(13.3cm x 4.4
Low Frequency Driver	4"(10.16 cm) black fiberglass cone
Suitable Amplifier Range	50-200 Watts
Max Power Handling	100 Watts
Binding Post Inputs	Push style accommodates wire up to 12AWG
Weight	6.02 lbs. (2.73 kg) each
Dimensions (overall size)	12.74" x 6.13" x 2.69" (32.36 x 15.56 x 6.82cm)
Required Wall Opening (includes tolerance)	11.87" x 5.25" (30.14cm x 13.34cm)
Projection From Wall Surface	0.28"(0.7cm)
Depth Behind Wall Surface	2.57"(6.52cm)