



6.5" Stereo In-Ceiling Speaker

IC6-ST

SKU: 155781 UPC: 810123023998

The IC6-ST in-ceiling speaker offers all the benefits of the IC6, with the added advantage of stereo performance from a single speaker. This design allows the speaker to provide stereo sound from a single speaker, ideal for use in small rooms such as offices, entryways, and kitchens. IC6-ST binding posts can also be bridged to deliver mono sound reproduction with wide dispersion. You can use the IC6-ST for nearly any application.

Solutions Meet Performance - Manufactured to the highest standards of quality and performance, the new Installer Series by MartinLogan is a line of affordable, high-performance, ultra-low-profile custom installation in-ceiling and in-wall speakers. Featuring titanium dome tweeters and mineral-filled polypropylene drivers, each model comes with a remarkably robust mounting-lock system and paintable micro-perf, bezel-free grilles for a nearly invisible installation. Two all-weather models extended usage to high humidity areas. Pre-installation brackets are available for all models and square grilles are available for select in-ceiling models.

Micro-Perforated Grilles - Installer Series speakers feature ultra-low profile, paintable, micro-perforated grilles with no visible bezel for a near invisible integration into any wall or ceiling. A series of powerful magnets hidden inside the speaker quickly secure grilles into place, reducing the risk of warping or damage during installation. To match modern aesthetics, optional square grilles are available for most in-ceiling models (excludes all-weather versions). **Robust Mounting-Lock System** - A simple, yet robust mounting-lock system allows quick, trouble-free installation. Pocketed screw holes help hold the drill steady, making installation a snap. When not in use, mounting locks are held securely within a self-contained housing. When moved into place, they couple the chassis firmly to the ceiling or wall, increasing the rigidity of surfaces. If ever removed, the locks retract and latch back in their housings. Each speaker includes a full-size installation template featuring quick-reference instructions, and die-cut guides for marking the cutout hole.

Frequency Response	52-20,000 Hz
Aiming	Rotate speaker
Recommended Amplifier Power	80 Watts (mono)
Recommended Amplifier Power (Stereo)	40 Watts (stereo)
Sensitivity	89dB
Impedance	Compatible with 4 ohms mono / 8 ohms stereo
Crossover Frequency	3,000 Hz

High Frequency Transducer	Two 0.75"(1.9cm) titanium domes
Low Frequency Transducer	Dual voice-coil 6.5"(16.5cm) mineral-filled poly cone
Binding Post Inputs	Push style accommodates wire up to 12AWG
Weight	4 lbs. (1.8 kg)
Dimensions (overall size)	8.7"x 3.46 (22.1 x 8.8cm)
Cut-Out Dimensions	7-3/4"(19.6cm) dia.
Projection From Wall Surface	0.31"(0.8cm)
Depth Behind Wall Surface	3.17"(8cm)
Square Grille (sold separately)	C6 & C6-ST Square Grille
Pre-install Bracket (sold separately)	C6 & C6-ST Bracket