



18/2 Stranded Shielded Cable 1000'
Spool - White

18/2SHP

SKU: 41121 UPC: 81007001853

2C/18 AWG STRANDED SHIELDED PLENUM, UL CMP/CL3P - WHITE - 1000 FT SPOOL

Applications:

Security Systems, Intercom Systems, Sound/Audio Systems, Power-Limited Controls. Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Features

- Multi-Conductor shielded low smoke PVC insulated stranded bare copper conductors, twisted with overall AL mylar shielding (with drain) and low smoke overall PVC jacket. Ripcord and sequential foot markings printed on jacket.
- CMP/FT6 Rated, FPLP, CL2P, CL3P
- 22-16 AWG: NEC FPLP/760, CMP/800, CL3P, CL2P/725
- 14-12 AWG: FPLP, CL3P
- ETL, c(ETL), RoHS, CE

Conductor	18 AWG 7 Strand SBC Cond.
Total Cable Weight	33 kg/km
Insulation	PVC
Shield	Foil Shield 0.625
Drain	24 AWG 7 Strand STC Cond
DC Resistance 25°C	7 Ohms / 1000 ft
Impedance	32 Ohms
Velocity of Prop	0.58
Final Diameter	0.160 inches
Jacket	PVC
Insulation Colors	Red & Black
Mutual Capacitance	77 pF/ft
Inductance.	1.3 mH/km
Cabled OD Avg	0.1
Ins Thickness	0.008
Jkt Thickness	0.015
Certified	UL CL2P/CL3P OR FPLP/CMP
Flame Rating	Plenum
Max Voltage	300V