



## Stranded Alarm Wire 500' Coil Pack - Green

22/2COIL-GN

SKU: 15504    UPC: 810070011703

### 2C/22 AWG STRANDED PVC COIL PACK Security Alarm Cable - 500 FT

SCPs Security Wire Coil Packs are very popular with installers because they are easier to work with than boxes or reels. These security wire coil packs come in 22 AWG with either 2 or 4 stranded bare copper conductors in 500 or 1000 ft lengths. SCP Security Wire Coil Packs are tangle-proof, take up less space, and because there is no box or spool, there is less waste and clean-up after the job.

Installation of our Security Wire Coil Packs saves time when pulling multiple wires. Because the wire pulls through the middle of the coil pack, installers can stack the coil packs and pull multiple wires in parallel for faster installation. SCP Security Wire Coil Packs with stranded conductor are available in 10 different PVC jacket colors. Our security wire coil packs are great for security, alarm, and control installations. All of our security wire coil packs are UL and Riser Rated.

#### Feature

- 22 AWG Stranded
- 2 Conductor
- Bare Copper
- Jacket: PVC
- Coil Pack
- Impedance: 78.5 Ohms
- Sequentially marked per 2FT
- UL and Riser Rated

#### Available in:

- Beige - 22/2COIL-BE
- Black - 22/2COIL-BK
- Blue - 22/2COIL-BL
- Brown - 22/2COIL-BN
- Green - 22/2COIL-GN
- Gray - 22/2COIL-GY
- Orange - 22/2COIL-OR
- White - 22/2COIL-WT
- Yellow - 22/2COIL-YL

Conductor	22 AWG 7x.0097 Bare Copper
Total Cable Weight	13 kg/km
Insulation	PVC
DC Resistance 25°C	17.6 Ohms / 1000 ft
Impedance	78.5 Ohms
Velocity of Prop	69 %
Final Diameter	0.114 inches
Jacket	PVC

Mutual Capacitance	22.8 pF/ft
Inductance	1.3 mH/km
Cabled OD Avg	0.084
Ins Thickness	0.006
Jkt Thickness	0.015
Certified	UL CL3R/CMR
Flame Rating	Riser
Max Voltage	300V
NEC Articles	800, 725
Min. Bend Radius/Minor Axis	.798 inches
Operating Temperature	-20°C to 60°C
Standard UL Temp	60°C
Package Weight	3.5 lbs / 1.59 kgs