



450Mbps Wireless N Router

TL-WR940N

SKU: 60707 UPC: 845973051464

What This Product Does: 450Mbps Wireless N Router TL-WR940N is a combined wired/wireless network connection device designed specifically for small business and home office networking requirements. With MIMO Technology, TL-WR940N creates an exceptional and advanced wireless performance, making it ideal for streaming HD video, VoIP and online gaming. Also, WPS button on the sleek and fashionable exterior ensures WPA2 encryptions, preventing the network from outside intrusions. **Wireless N Speed & Range:** Complying with the IEEE 802.11n standard, TL-WR940N can establish a wireless network and get up to 15X the speed and 5X the range of conventional 11g products. Also, with transmission rates up to 450Mbps, it shows more excellent abilities of mitigating data loss over long distances and through obstacles in a small office or a large apartment, even in a steel-and-concrete building. Above all, you could easily pick up the wireless network during long-distance connection where legacy 11g products may not! **Better Wireless Performance:** The router has the speed to work smoothly with almost any bandwidth intensive application including VoIP, HD streaming, or online gaming, without the lag. Using its powerful N technologies, the router is also able to mitigate data loss over long distances and through obstacles turning your home and even your yard into one big hot - spot.

Features

- Input Type RJ-45 (Ethernet Cable) supported by neighborhood cable broadband ISPs such as Hathway, ACT, Tikona, Airtel Fibrenet, MyWorld, Nextra, Siti Cable, You Broadband, Spectranet etc
- Product Type: Routers, This Router Does Not Include Modem and works well with Cable Broadbands
- Free Express Shipping to your doorstep. You don't have to pay anything extra!!
- This product is imported from USA - It is a 100% genuine product
- The price includes import custom duties and taxes

HARDWARE FEATURES:	
Interface	4 10/100Mbps LAN PORTS 1 10/100Mbps WAN PORT
Button	Wireless On/Off Button, WPS/Reset Button, Power On/Off Button
Antenna	3*5dBi Fixed Omni Directional Antenna
External Power Supply	12VDC / 1A
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H)	9.1 x 5.7 x 1.4 in. (230 x 144 x 35mm)
WIRELESS FEATURES:	
Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 450Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)

Reception Sensitivity	270M: -68dBm@10% PER 130M: -68dBm@10% PER 108M: -68dBm@10% PER 54M: -68dBm@10% PER 11M: -85dBm@8% PER 6M: -88dBm@10% PER 1M: -90dBm@8% PER
Transmit Power	CE: <20dBm(2.4GHz) FCC: <30dBm
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128/152-bit WEP / WPA / WPA2,WPA-PSK / WPA2-PSK
SOFTWARE FEATURES:	
Quality of Service	WMM, Bandwidth Control
WAN Type	Dynamic IP/Static IP/PPPoE/ PPTP(Dual Access)/L2TP(Dual Access)/BigPond
Management	Access Control Local Management Remote Management
DHCP	Server, Client, DHCP Client List, Address Reservation
Port Forwarding	Virtual Server,Port Triggering, UPnP, DMZ
Dynamic DNS	DynDns, Comexe, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec (ESP Head)
Access Control	Parental Control, Local Management Control, Host List, Access Schedule, Rule Management
Firewall Security	DoS, SPI Firewall IP Address Filter/MAC Address Filter/Domain Filter IP and MAC Address Binding
Protocols	Support IPv4
OTHERS:	
Certification	CE, FCC, RoHS
Package Contents	TL-WR940N Power supply unit Resource CD Ethernet Cable Quick Installation Guide
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™ or Windows 7, Windows8/ 8.1/10 MAC® OS, NetWare®, UNIX® or Linux
Environment	Operating Temperature: 0?~40? (32?~104?) Storage Temperature: -40?~70? (-40?~158?) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing