



16/4 65 Strand Speaker Wire 500' Box - Black

16/4OFC-BK

SKU: 40387    UPC: 810070018283

4C/16 AWG 65 STRAND OXYGEN FREE COPPER SPEAKER CABLE, PVC JKT- 500 FT BOX- BK

### Applications:

High End Professional Audio In-Wall Rated, Home Theater Grade, Speaker Audio

### Construction:

This cable consists of high strand count insulated oxygen free copper conductors in twisted pair construction (unshielded) with easy strip PVC jacket. Cable includes SCP Cable Labeling System with sequential foot/meter markings, and room/zone/outlet designations for easy cable identification.

#### Features

- 99.97 % Oxygen Free bare copper conductors
- High Strand Count
- Ultra Flexibility
- Easy Pull Coated PVC jacket
- Easy Strip Construction
- UL Listed, CMR In-Wall Rated, NEC CL2, and CEC CMG FT4; RoHS, CE

<b>Construction Characteristics:</b>	
<b>Conductor:</b>	
Material	Stranded Bare Copper
Size	16AWG X 4C(2.11mm <sup>2</sup> )
Construction	65/0.16mm +/-0.004mm
<b>Insulation:</b>	
Material	PVC
Min. Thickness	0.30mm
AVG. Thickness	0.33mm
Diameter	2.0mm +/-0.10mm
Colors	Black & Red & Green & White
<b>Jacket:</b>	
Material	PVC
Min. Thickness	0.54mm
AVG. Thickness	0.60mm
Diameter	6.1mm +/-0.20mm
Rip Cord	Nylon
Color	Per request
Bend Radius	Min 15D/95mm
<b>Electrical &amp; Physical Characteristics:</b>	

Operating Temperature Range	- 20°C + 75°C
Conductor Resistance	Max 15.5ohm/km at 20°C
Insulation Resistance	Min 50M Ω*km at 20°C
Dielectric Strength	Min AC1.5KV
Rated Voltage	Max 300 Volts
<b>Insulation:</b>	
<b>Unaged:</b>	
Tensile Strength	13.8Mpa
Elongation	100%
<b>Aged:</b>	
Tensile Strength	11.7Mpa(100°C 168h)
Elongation	50%(100°C 168h)
<b>Jacket:</b>	
<b>Unaged:</b>	
Tensile Strength	13.8Mpa
Elongation	100%
<b>Aged:</b>	
Tensile Strength	11.7Mpa(100°C 168h)
Elongation	50%(100°C 168h)
<b>Packaging:</b>	
Approx Weight	11.8Kgs/26.014lbs
Approx Dimension (mm)	320X260X320
Package	500ft/152m - Box
Packages per pallet	36