



6-Input, 240-Watt Mixer Amplifier

AA240G

SKU: 177798 UPC: 61207966269

The AA240G is a 240 Watt six input multi load impedance mixer amplifier that is engineered with many unique features to assist the contractor or installer in today's commercial business audio environment. It is designed for distributed paging and background music (BGM) systems, small to medium sound masking systems, and in applications where music on hold (MOH) plus paging is required.

With four microphone / line inputs and two stereo line input, the A240G will accommodate a variety of input sources including paging microphones, CD players, and digital music receivers. This mixer amplifier features VOX (Voice Operated Mute) and contact closure muting, tone control, Line out and Zone 2 Output. The AA240G offers a very unique Bridge In / Out feature to allow combining of multiple amplifiers in ballroom applications without the need for external relays. VCA remote level control circuitry is included which may be assigned to the BGM input or globally for the entire amplifier.

The output power of output power of the AA240G will match nicely with AtlasIED FAP, SM, SD, and GD Series loudspeakers. 25V, 70.7V, 100V, and 8 Ω outputs are provided.

Features

- 240 Watt 6 Channel Mixer Amplifier
- 4 Mic/Line Inputs with Phantom On/Off per Mic and 2 Stereo Summing AUX Inputs
- Bridge In/Out Circuit with Balanced Link / Internal Relay to Engage Circuit is Perfect for Small Room Combining Systems Eliminating the Need for External Electronics
- Pre Out / Power Amp In for Patching External Processors
- Remote or VOX Mute Capabilities
- Special Low Cut Filter is 6dBu/octave at 400Hz and also Bypasses Front Panel Bass Control to Allow Use with Paging Horns like APX40TN and AP-15T
- VCA Control Assignable to Input 6 Line Level (BGM) Input or Global for the Mix Bus
- Zone 2 MOH Out from CH6 Line Source
- UL60065 Listed

Frequency Response	50Hz - 20kHz
Power Output	240-Watts 8 Ω /25V/70.7V/100V
Connector Type	Phoenix and RCA
Output Power	240 Watts
Rack Units	1
Height	3 1/2" (9 cm)
Width	17" (43.1 cm)
Depth	9 1/2" (24.1 cm)
Shipping Weight	16.5 lbs (7.5 kgs)
Safety Listed	UL60065 Standard, CE
Voltage Compatibility	100V - 240V