



# resideo

## Wireless Combination Magnetic Contact & Shock Sensor

5819S

SKU: 65178    UPC: 886618220593

Add the 5819S Wireless Shock Sensor and Transmitter from Honeywell to your alarm system. This device offers two points of protection thanks to a wireless magnetic contact and shock sensor functionality to ensure adequate protection at your doors and windows. The magnetic contact detects open and closed conditions of your doors and windows, while the built-in shock sensor detects abrupt, forcible attempts at entry. The shock sensor typically delivers shock protection in a 5-6 radius. Additionally, auxiliary terminals are included should you need a third protection point.

This device is omni directional, so it offers flexible mounting solutions. A CR123 battery, adhesive tape, magnet, and mounting hardware are included.

### Features

- Suitable for alarm systems that support Honeywell 5800 Series wireless devices
- 40% smaller than previous model
- Adhesive tape & mounting hardware included
- Includes auxiliary terminals for a third protection point

<b>General:</b>	
Shock Protection	Typical Shock Protection Area: 10 to 12' (3.05 to 3.66 m) Radius: 5 to 6' (1.52 to 1.83 m)
Voltage	3 VDC
Battery Type	1 x CR123 lithium
Battery Manufacturer	Duracell or Panasonic only
Terminals	Auxiliary terminals
LED Indicators	Yes
Operating Temperature	32 to 120°F (0 to 49°C)
Storage Temperature	-4 to 140°F (-20 to 60°C)
Operating Humidity	Up to 95% (non-condensing)
Certifications	cETLus listed to UL 639 standard for intrusion detection units ULC S306 intrusion detection devices UL 634 guide for the investigation of connectors and switches for use with burglar alarm systems
Dimensions (D x H x W)	1.19 x 3.06 x 1.56" (30.23 x 78 x 40 mm)
Weight	Without Battery: 0.1 lb (2.8 g)
<b>Packaging Info:</b>	
Package Weight	0.25 lb
Box Dimensions (LxWxH)	4.75 x 1.75 x 1.0"