



DM40 Slim Tower Speaker

DYMEENSION DM40

SKU: 181248 UPC: 747192137120

The Definitive Technology Dymension DM40 Slim Tower Speaker features custom aluminum oxide tweeters for explicit voice, four 4.5" midrange woofers with composite polymer cones to produce better midrange detail, and long-throw surrounds for low-end performance. A slim and acoustically tuned cabinet allows the speaker to fit into any room setting and deliver impressive performance. Fully balanced bipolar arrays of DM40 are adjusted to optimize for room placement and hold a rear-array attenuation switch for near-wall placement.

Pair this speaker with the DM20 Slim Center Channel Speaker and DM95 on-wall speakers (sold separately) to build an ultimate surround setup and deliver dynamic sound. Be it onscreen movie drama, melodies of your favorite singers, or hearing the sonic details while gaming, this high-performing speaker envelops you from every angle and transports you inside every scene and song. The consistent sound across Definitive Technology gives you the flexibility to mix and match Dymension, Dymension CI, and Mythos speakers, which can be voice-matched to design a complete home system.

Features

- Fully balanced bipolar driver array for truly enveloping sound
- Acoustically optimized, ported enclosure for smooth bass and clear midrange
- Aluminum oxide tweeter produces crisp, sparkling highs
- 4.5" long-throw drivers deliver detailed, balanced sound with superior low end
- Atmos/DTS:X ready—add optional DM95 surround speaker
- Slim cabinet design for unobtrusive room integration
- Rear-array attenuation switch for near-wall placement
- Timbre-matched for use with other Definitive Technology speakers
- Foot spikes and pads allow versatile placement and leveling
- Understated design disappears when the lights are low

| | |
|------------------------------------|---|
| Dimensions (H x W x D) | 37.4 x 10.3 x 10 in. |
| Weight | 38.1lbs |
| Color | Black |
| Grille Material | Acoustically transparent black cloth (not removable) |
| Tweeter | (2) 1 in. aluminum oxide dome |
| Midrange/Midbass | (4) 4.5 in. woofers |
| Enclosure Type | Ported |
| Bipolar Array | Fully balanced, adjustable |
| Bipolar Array Adjustment | Rear tweeter switch: 0dB, -6dB |
| Frequency Response | 38 Hz–30 kHz (-10dB) 55 Hz–23 kHz (-3dB) |
| Nominal Impedance | 4? (8? compatible) |
| Sensitivity | 87dB (2.83V/1m) |
| Recommended Amplifier Power Rating | 50–250W |
| Included Accessories | (4) Adjustable hard floor glides (4) Adjustable carpet spikes |