



6.5" Ceiling LoudSpeakers Transducer Assembly

CONTROL-26CT

SKU: 102798 UPC: 50036904087

The Control 26CT is a powerhouse ceiling speaker containing a coaxially mounted 6.5" woofer and 3/4" titanium-coated tweeter, able to deliver maximum sound level over a wide coverage area. The Control 26CT includes a multitap transformer for a 70V or 100V line distribution system.

Features:

- Coaxially mounted 165 mm (6.5 in) woofer with butyl rubber surround and 19 mm (.75 in) titanium coated
- High power, wide frequency response and low distortion for high sound level capability.
- Packaged with grille, backcan and tile rails for fast installation and easy dealer stocking.

Frequency Range (-10dB)	75 Hz - 20 kHz
Power Rating	See transformer taps
Transformer Taps	60W, 30W, 15W (& 7.5W @ 70V)
Coverage Angle	110° conical
Maximum SPL (1m)	107 dB (low-impedance, 113 dB peak)
Drivers	LF Driver: 165 mm (6.5 in) HF Driver: 19 mm (¾ in)
Input Connectors	Removable 4-pin locking connector with screw-down terminals.
Dimensions (H x Dia)	210 mm x 252 mm (8.3 in x 9.9 in)
Net Weight (each)	4.2 kg (10 lbs)
Shipping Weight (pair)	9.7 kg (21 lbs)
Safety Agency	Suitable for use in air handling spaces per UL1480, UL2043, NFPA90 & NFPA 70. S7232/UL Listed, Signaling Speaker. Transformer UL registered per UL1876. In accordance with IEC60849/EN60849.
Backcan	formed steel (included "blind-mount")
Baffle/Rim	Medium impact polystyrene, fire rated UL94V-0
Ceiling Cutout Size	220 mm (8.75 in) diameter (cardboard cutout template included)
Included Accessories	C-shaped support backing plate 2 tile support rails (fits both 2 x 4 ft or 600 x 1200 mm tiles) Cutout template Paint shield Removable locking wiring connector
Plenum Usage	Yes, backcan included