



6.5" Compact Control Monitor LoudSpeakers

CONTROL-5

SKU: 164778 UPC: 50036903462

The Control 5 is a high performance, wide range control monitor suitable for use as the primary sound source in a variety of applications.

Features

- Sensitivity: 89 dB SPL, 1 W, 1 m (3.3 ft)
- High power handling (175 W pink noise) with integral protection circuit network.
- Molded enclosure with shielded magnet structure.
- 165 mm (6.5 in) low frequency loudspeaker.
- 25 mm (1 in) pure titanium dome tweeter.

Frequency Response (± 3 dB)	75 Hz to 20 kHz
Power Capacity	175 W
Sensitivity	89 dB SPL, 1 W, 1 m (3.3 ft)
Crossover Frequency	3 kHz
Directivity Factor (Q)	2.8
Directivity Index (DI)	4.5
Dimensions (H x W x D)	(H) 387 mm x (W) 251 mm x (D) 229 mm (15.25 in x 9.875 in x 9 in)
Polarity	Positive Voltage to + terminal causes outward low frequency cone motion
Enclosure	Polypropylene structural foam
Net Weight (each)	4.5 kg (10 lbs.)
Shipping Weight (pair)	11 kg (24 lbs.)
Note	Molded of dense polypropylene Accessory attachment points on rear of the enclosure are 1/4 x 20 threaded brass bushings
Maximum SPL (1m)	111 dB continuous, 117 dB peak
Drivers	LF Driver: 165 mm (6.5 in) HF Driver: 25 mm (1 in)
Input Connectors	Spring-loaded terminals
Grille	Zinc-plated steel
Mounting Hardware	Mounting points -- no bracket included.
Amplifier Power Rating	175 W