



# resideo

Wireless Door / Window Sensor (Mini 2)

PROSIXMINI2

SKU: 170123    UPC: 194160003985

## Encrypted Protection, Now Easier to Install

With a range up to 300 feet and 128-bit AES encryption, the Two-Way Mini Wireless Window and Door Sensor provides a high level of security to the furthest areas of your customers' homes or yards and now comes in a mini size for easier installation.

## Features

- SiX Two-Way Wireless Technology employs 128-bit AES encryption
- System Health Check feature allows monitoring of device signal strength, sensor settings, temperature and battery life remotely via AlarmNet 360
- Devices can be configured remotely as needed, reducing the need to schedule on-site visits
- Reduce truck rolls with user-replaceable batteries and the ability to remotely adjust sensor parameters and download software updates.
- Mounting hardware is included
- Transmission Range - 300 ft (92 meters) plus
- LED Indicators - Yes
- Temperature Sensing Capable - Yes
- Frequency - 2.4 GHz
- Encryption - 128-bit AES
- Power Requirements - 3 volt CR2 Lithium Battery, Qty 1 (Panasonic CR2, Duracell CR2, Energizer CR2 or Evergreen CR2 (Qty 1)
- Tamper-protected
- Dimensions – 1.1" high x 1.6" wide x 3.1" long
- Approval Listings - FCC/IC, ETL Listed to UL 639, cETL Listed to ULC-S306

**PROSIX WIRELESS DOOR/WINDOW SENSOR (MINI 2) Power Supply Battery Powered For Use With ProSeries WiFi Yes Tamperproof Yes Application Security System Sensors Warranty 2 Years Approvals and Standards ETL Listed Includes Mounting hardware Product Height 0.8 in, 20.3 mm Product Length 2.9 in, 74 mm Product Width 1.2 in, 30.5 mm Color White Ambient Relative Humidity (Max) 95% Non-condensing Battery Size 3V, Panasonic CR2, Duracell CR2, Energizer CR2, Evergreen CR2 Battery Type Lithium Number of Batteries 1 Ambient Operating Temperature (Max) 122 °F, 50 °C Ambient Operating Temperature (Min) 32 °F, 0 °C Mounting Location Surface Mount**