



# ELURA

## 6.5" Coaxial Two-Way Pendant Speaker

G6.5PEND-BK

SKU: 184671    UPC: 81993201410

The Elura line of pendant speakers offers two full-range 2-way products and one subwoofer suited for a wide variety of foreground and background applications such as restaurants, retail, concourses, transportation terminals, worship facilities, etc. All three products are designed to work with 8 Ohm or 70/100V amplifiers with a wide variety of transformer settings for the desired sound level requirement.

### Features

- 2-Way Pendant Loudspeaker
- 6.5" Fiberglass Woofer with Rubber Surround
- 0.75" Black Aluminium Tweeter with Neodymium Magnet
- Speaker Dispersion Angle: 130° Conical
- Frequency Response: 60Hz-20KHz  $\pm$  3db
- Power: 80 watts RMS
- 5/10/15/20W 70V taps plus an 8 $\Omega$  bypass
- Aluminum Grille (Non-removable)
- 15' Gripple hardware included
- Dimensions: 9" x 13.15"

	<a href="#"><u>G6.5PEND-BK</u></a>	<a href="#"><u>G8PEND-BK</u></a>	<a href="#"><u>G8PENDSUB-BK</u></a>
<b>Description</b>	6.5" Coaxial, 2-way pendant loudspeaker	8" Coaxial, 2-way pendant loudspeaker	8" Pendant subwoofer
<b>Woofer Size</b>	6.5 inch	8 inch	8 inch
<b>Woofer Material</b>	Fiberglass cone with rubber surround	Fiberglass cone with rubber surround	Fiberglass cone with rubber surround
<b>Woofer Voice-Coil Size</b>	30.5mm	30.5mm	38.5mm
<b>Tweeter Size</b>	0.75 inch	0.75 inch	n/a
<b>Tweeter Material</b>	Black aluminium	Black aluminium	n/a
<b>Tweeter Magnet</b>	Neodymium	Neodymium	n/a

<b>Recommended Amplifier Power</b>	80 watts RMS	120 Watts RMSI	150 watts RMS
<b>Frequency response</b>	60Hz-20KHz ± 3db	45HZ-20KHz ± 3db	45Hz - 500Hz ± 3db
<b>Sensitivity level</b>	89db @ 1W at 1 meter	91db @ 1W at 1 meter	89db @ 1W at 1 meter
<b>Transformer taps &amp; Thru Setting</b>	5W/10W/15W/20W 70V taps 80hm bypass	5W/10W/20W/30W 70V taps 80hm bypass	15W/30W/45W/60W 70V taps 80hm bypass
<b>Speaker dispersion angle (-6dB)</b>	130° Conical (500Hz-5kHz average)	110° Conical (500Hz-5kHz average)	Omni (45Hz-500Hz)
<b>Grille</b>	Push-On Aluminium	Push-On Aluminium	Push-On Aluminium
<b>Dimensions (W x D x H)</b>	9" x 13.15"	10.63" x 15.25"	10.63" x 15.25"
<b>Weight</b>	8.4 lb (5.25kg)	12.3 lb (5.6kg)	12.3 lb (5.6kg)