



VICTROLA

Hi-Res Onyx Turntable

VPT-1500-BLK

SKU: 184745 UPC: 810033111846

Enjoy the vibrant sound of vinyl records with the Victrola Hi-Res Onyx turntable. Go wireless with the best-in-class aptX™ Adaptive Bluetooth connectivity or wired with switchable preamp standard RCA outs (RCA cables included), allowing you to listen to your favorite records with stunning clarity.

The sleek aesthetic, simple setup, and quality construction result from a purpose-built design focused on the listener experience. The Hi-Res Onyx includes an Audio Technica AT-VM95E cartridge, metal components, and an aluminum tonearm featuring a custom-designed, removable headshell. With the Victrola Hi-Res Onyx, you can effortlessly lower the tonearm and enjoy listening to your records with exceptional quality; Connect wirelessly to any Bluetooth or aptX™ enabled speakers, headphones, or wired to your favorite amplifier or powered speakers.

Features

- aptX™ Adaptive and HD Audio - Built-in Hi-Res Bluetooth Audio Transmission to your compatible speakers and headphones (Fully backward compatible with all Bluetooth devices)
- Gold-plated RCA Outs – For wired listening for those that would also like to listen to analog sound
- High-Quality Materials – Low-resonance veneered MDF plinth with premium metal turntable components and platter
- Premium Tonearm and Easy Set Counterweight – Carbon fiber tonearm with custom-designed removable headshell and adjustable counterweight for simple set up
- Audio Technica AT-VM95E Cartridge – Brings balanced and distortion-free playback
- User-Friendly Features – Front-facing controls, switchable preamp with traditional analog RCA outputs and auto-stop sensor to prevent stylus wear

Power Input	AC 100-240V - 50HZ/60HZ
Supported Bluetooth Codecs	QUALCOMM® APTX, ADAPTIVE, APTX HD, APTX, SBC
Outputs	RCA (built-in preamp), Phono
Material	MDF, ALUMINUM, PLASTIC
Colors	Black, silver
Dimensions	L 16.93" X W 14.25" X H 4.53"
Weight	12.48 Lbs
Drive Method	Belt-drive
Platter	Die-cast aluminum
Cartridge	Audio Technica AT-VM95E
Motor	DC Servo-Controlled
Speeds	33-1/3 RPM & 45 RPM
Phono Pre-Amp Gain	35 DB Nominal, RIAA Equalized
Signal-to-Noise	>45 DB
Wow & Flutter	< 0.175
Tonearm Length	225 MM
Overhang	18.5 MM

Tracking Error Angle	<2 Degrees
----------------------	------------