



# SAVANT

## Metropolitan Wireless Bi-Phase Dimmer V2

WID-SWB102V2-00

SKU: 185389    UPC: 863184007346

The Savant Metropolitan Wireless Bi-Phase Dimmer is designed to be manually set to forward or reverse phase dimming types during configuration, allowing for the elimination of visible calibration during reset or power-on. Buttons on the Bi-Phase Dimmer can be programmed to activate Scenes including lighting, shades, climate, AV and other services - replacing traditional dimmers with intuitive, multi-button Scene control. Supports 5 GHz and 2.4 GHz Wi-Fi bands. New Roaming Assisted Discovery (RAD) allows multiple keypads to be provisioned to the local network. Simply provision one keypad, enable RAD, then join the other keypads to the network with the push of a button. Faceplates sold separately.

**NOTE:** Does not support Magnetic Low Voltage (MLV) loads. For MLV loads, ensure that a Forward Phase keypad with MLV compatibility is used

### Features

- Supports Forward Phase or Reverse Phase dimming, selected and set manually during configuration
- Ambient Light Sensor - Detects the level of ambient light in the room and adjusts the LED brightness on the front panel
- Works with the auxiliary control for wired 3-way applications
- Fits standard decorator-style wall plates
- Communicates with an 802.11 b/g/n wireless network
- Supports 5 GHz and 2.4 GHz Wi-Fi bands
- Roaming Assisted Discovery (RAD) - Makes provisioning keypads faster, and more efficient
- Simple to configure and deploy using Blueprint Lighting & Shades Device Manager

|                       |   |
|-----------------------|---|
| Temperature           | 32° to 104° F (0° to 40° C)                   |
| Humidity              | 10% to 90% Relative Humidity (non-condensing) |
| Input                 | 120V AC at 60 Hz                              |
| Power: Load (Max)     | 550W 5A @ 120V AC                             |
| Rated Impulse Voltage | 2500V   |
| Height                | 4.13in (10.50cm) Shipping 7.0in (17.78cm)     |
| Width                 | 2.36in (6.00cm) Shipping 4.5in (11.43cm)      |
| Depth                 | 1.57in (3.99cm) Shipping 3in (7.62cm)         |
| Weight                | Shipping 0.60lb (0.272kg)                     |