



MAX In-Wall 6.5" Speaker

DW-65 Max

SKU: 185982 UPC: 747192140618

Dymension CI DW-45 MAX and DW-65 MAX in-wall speakers deliver precise sound while virtually vanishing into any room. Our highest-performance in-wall speakers feature premium woofers and tweeters; discreet, flush-mount designs; and IP55-rated protection against water and dust. Flagship Definitive Technology acoustic innovations like BDSS™ (Balanced Double Surround System) woofers with Linear Response Waveguide™, all-new pivoting aluminum oxide dome tweeters, and advanced crossover networks deliver rich, balanced sound with effortless bass and crystal clear highs, and an innovative toolless system makes installation a snap. It's never been easier to experience the thrills of enveloping sound in any space, indoors or out. Combine timbre-matched Dymension™, Dymension CI, and Mythos® speakers and Descend Series subwoofers to design the high-performance home theater system of your dreams.

Features

- Audiophile-quality sound in an in-wall bipolar speaker
- Effortless, toolless installation; pre-construction brackets available
- Bipolar driver array produces immersive, room-filling sound
- Pivoting tweeter aims highs where you want them
- Tailor sound with three-way high-frequency adjustment switch
- Advanced crossover optimizes drivers for balanced sound
- Low-profile, borderless design vanishes into decor
- CI Series is IP55-rated for use outdoors and in high-humidity spaces
- Timbre-matched with Dymension™ and Mythos® speakers
- 4.5" (DW-45 MAX) 6x9 aspect-ratio and 6.5" (DW-65 MAX) variants

Product Dimensions (W x H x D)	9.15 x 13.68 x 3.95 in (232.4 x 347.4 x 100.3 mm)
Cut-Out Dimensions (W x H)	7.92 x 12.45 in (201.2 x 316.2 mm)
Mounting Depth	3.66 in (92.9 mm)
Weight	5.09 lbs
Grille Material	Micro-Perforated Magnetic Grille
Tweeter	1 in Aluminum Oxide Dome Tweeter
Midrange/Midbass	6.5 in Mineral-Filled Poly BDSS™ with Linear Response Waveguide™
Frequency Response	34 Hz–30 kHz (-10 dB) 56 Hz–25 kHz (-3 dB)
Nominal Impedance	6?
Sensitivity	85dB (2.83V/1m)
IP Rating	IP55
Included Accessories	Grille, Literature Pack (QSG/ Registration Card/Warranty), Hole Cutting Guide

