



ILLUMIVUE™ BY MSTR

8MP IP Turret Camera with NightLight and LED Defender Technology


IP8T-RB-DNL

SKU: 186313 UPC: 81993201427

Illumivue IP8T-RB-DNL 8MP IP Turret Camera with NightLight and Red/Blue LED Defender Technology.


Features

- 8MP (3840*2160)@ 30/25(default)fps; 5MP (3072*1728)@ 30/25fps; 4MP (2560*1440) @30/25fps; 2MP (1920*1080) @30/25fps
- High quality image with 8MP, 1/2.8"CMOS sensor
- Extreme Low Light - 0.0005 Lux
- Ultra 265, H.265, H.264, MJPEG
- Intelligent perimeter protection includes cross line, intrusion, enter area, leave area detection
- Based on target classification, smart intrusion prevention significantly reduces false alarms caused by leaves, birds and lights, etc. accurately focusing on humans, motor vehicles and non-motor vehicles
- Intelligent People Flow Counting and Crowd Density Monitoring
- Auto Scene Match (ASM) (Only WDR)
- 130dB true WDR technology enables clear images in a strong light scene
- Red and Blue Strobe Alarm
- Supports 9:16 Corridor Mode
- Alarm: 1 in/1 out, Audio: 1 in/1 out, Built-in Mic and Speaker
- Smart IR, up to 30m (98.4 ft) IR distance
- Supports 256 GB Micro SD card
- IP67 protection



Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



Sensor	1/2.8", 8.0 megapixel, progressive scan, CMOS
Minimum Illumination	Color: 0.0005 Lux (F1.0, AGC ON) 0 lux with IR on
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
WDR	130dB
S/N	>56dB

Lens	2.8mm @ F1.0
Iris	Fixed
Field of View (H)	106.5 degrees
Field of View (V)	57.9 degrees
Field of View (D)	132
IR Range	Up to 98.4 ft
Warm Light Range	Up to 98.4 ft
Wave Length	850nm
Smart intrusion prevention	Supports false alarm filtering: Cross Line Detection, Intrusion Detection, Enter Area Detection, Leave Area Detection
Statistical Analysis	Supports People Flow Counting and Crowd Density Monitoring
Basic Detection	Motion Detection, Ultra Motion Detection, Tampering Alarm, Audio Detection
General Function	Watermark, IP address filtering, tampering alarm, alarm input, alarm output, access Policy, ARP protection, RTSP authentication, user authentication
Audio 1/0 Input	impedance 35kΩ; amplitude 2V [p-p]
Audio 1/0 Output	impedance 6000; amplitude 2V [p-p]
Built-in Mic	Supported
Build-in Speaker	Supported