



ILLUMIVUE™ BY MSTR

8MP Turret IP Camera with NightLight

IP8T-DNL

SKU: IP8T-DNL

Introducing the Illumivue IP8T-DNL 8MP Turret IP Camera with NightLight, a cutting-edge surveillance solution that combines superior image quality, advanced features, and enhanced night vision capabilities. With its state-of-the-art technology and durable design, this camera offers uncompromising security for various applications.

The 8MP IP8T-DNL camera captures highly detailed and crystal-clear images, ensuring that every critical detail is recorded with precision. Whether you're monitoring a large area or focusing on specific points of interest, this camera delivers exceptional visual clarity, providing you with sharp and accurate footage.


This camera boasts NightLight technology, which features two bright LED lights and extra-large aperture that greatly improves the camera image in near-dark situations while deterring criminals. This innovative feature ensures that you capture detailed and accurate images even in complete darkness, providing you with 24/7 surveillance coverage.

Designed with a sturdy and compact turret form factor, the IP8T-DNL blends seamlessly into any environment. Its discrete appearance makes it an ideal choice for both indoor and outdoor installations, ensuring reliable surveillance coverage without compromising aesthetics.

The Illumivue IP8T-DNL 8MP Turret IP Camera with NightLight is a powerful and versatile security solution. Its exceptional image resolution, innovative NightLight technology, robust turret design, and intelligent alerts make it the perfect choice for those seeking advanced surveillance capabilities.


Features

- 8MP IP Turret Camera
- NightLight - LED lights give a boost in low light scenarios that helps enhance image quality.
- Active Defender - Can warn intruders with flashing white light strobe lights and audible sound.
- 120DB True WDR - Wide Dynamic Range for scenes with high-contrast lighting
- 2.8mm@F1.6 Lens
- 0.003 Lux Extra Low Light
- 98ft (30m) IR LED Range
- Advanced Analytics - Supports line cross, intrusion, enter area, leave area, face detection, face capture, motion, tampering & audio detection
- Corridor Mode - helps to effectively reduce invalid monitoring regions and shows more details
- Ultra 265, H.265, H.264, MJPEG
- Built-In Speaker
- Pre-Recorded Audio Message Capable
- Up to 256GB Micro SD card slot
- Cloud Software Updates
- 835ft PoE Connection Range
- IP67 Protection (Indoor/Outdoor)
- NDAA-Compliant
- Onvif Support (Profile S, Profile G, Profile T)



Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



| | | | | | | |
|----------------------|--|------------|----------------|---------------|-------------------|--|
| Camera | | | | | | |
| Sensor | 1/2.8", 8.0 megapixel, progressive scan, CMOS | | | | | |
| Lens | 2.8mm@F1.6 | | | | | |
| DORI Distance | Lens (mm) | Detect (m) | Observe (m) | Recognize (m) | Identify (m) | |
| | 2.8 | 89.9 | 34.8 | 17.4 | 8.7 | |
| Angle Of View (H) | 106.7° | | | | | |
| Angle Of View (V) | 57.1° | | | | | |
| Angle Of View (O) | 115.7° | | | | | |
| Adjustment Angle | Pan: 0° ~ 360° | | Tilt: 0° ~ 80° | | Rotate: 0° ~ 360° | |
| Minimum Illumination | Colour: 0.003Lux (F1.6, AGC ON) 0Lux with IR on | | | | | |
| IR Range | Up to 30m (98ft) IR range | | | | | |
| IR On/Off Control | Auto/Manual | | | | | |
| WDR | 120dB | | | | | |
| Edge Storage | Micro SD, up to 256 GB | | | | | |
| Built-in Mic | Supported | | | | | |
| Built-in Speaker | Supported | | | | | |

| | |
|-------------------|--------------------------------|
| Video | |
| Video Compression | Ultra 265, H.265, H.264, MJPEG |
| Video Stream | Triple streams |
| | |

| | |
|-------|--|
| Image | |
|-------|--|

| Camera | |
|-------------------------|--|
| Digital Noise Reduction | 2D/3D DNR |
| Smart IR | Supported |
| Dewarping | Supported |
| Flip | Normal/Vertical/Horizontal/180°/90°Clockwise/90°Anti-clockwise |

| General | |
|--------------------|---|
| Certifications | FCC CFR 47 Part 15 EN 55032:2015 EN 55024:2010 EN 61000-3-2:2014 EN 61000-3-3-2013 IEC 62368-1 EN 62368-1 UL 62368-1 |
| IP Rating | IP67 |
| Power | DC 12V±25%, PoE (IEEE 802.3af) |
| Dimensions (Ø x H) | ? 111 x 95mm (?4.4" x 3.7") |
| Weight | 0.48kg (1.058lb) |