



ILLUMIVUE™ BY MSTR

2MP TVI Turret Camera with NightColor & NightLight

TVI2T-NC-NL

SKU: 187386 UPC: 81993201445

Illumivue TVI2T-NC-NL 2MP TVI Turret Camera with NightColor & NightLight


Features

- High quality imaging with 2MP resolution
- TVI/AHD/CVI/CVBS
- Supports IR-cut filter with auto-switch (ICR)
- Smart Dual Light (only TVI)
- 3D noise reduction technology delivers clean and sharp images
- Supports 180 horizontal flip, 180 vertical flip
- OSD configuration menu, easy to operate
- IP67 waterproof and dustproof design, high reliability
- OSD configuration menu in 11 languages
- Built-in microphone for high quality audio transmission via coaxial cables



Download the Illumivue App

Access, Set-up, and Manage Illumivue surveillance products through your network via iOS, Android or Windows.



Camera

Sensor	1/3.0", 2.0 megapixel, CMOS
Lens	2.8mm@F1.6
Angle Of View (H)	100.9°
Angle Of View (V)	55.5°
Angle Of View (D)	121.8°
Minimum Illumination	Colour: 0.003 lux (F1.6, AGC ON) 0 lux with Light on
IR Range	Up to 40m (131.23ft) IR range

Camera	
LED On/Off Control	Auto/Manual
WDR	DWDR
Built-in Mic	Supported
Built-in Speaker	N/A

Video	
Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame Rate	TVI: 1080P@25fps (default), 1080P@30fps; 720P@25fps, 720P@30fps AHD: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVI: 1080P@25fps, 1080P@30fps; 720P@25fps, 720P@30fps CVBS: PAL, NTSC

Image	
Exposure Mode	Four modes: Global (default), BLC, HLC, DWDR
Day/Night	Three modes: Auto (default), Day, Night
Digital Noise Reduction	2D/3D
Flip	Supports 180°horizontal flip, 180°vertical flip

General	
Certifications	CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035); FCC (FCC 47 CFR part15 B)
IP Rating	IP67
Power	DC 12V±25%
Dimensions (Ø x H)	? 110.53 x 97.60mm (?4.3" x 3.8")

Camera	
Weight	0.24kg (0.53lb)