



SLM XL Ultra-Slim On-Wall Speaker

MOTSMLXL

SKU: 155832 UPC: 877929009311

The slender Motion® SLM XL speakers features an advanced resolution Folded Motion tweeter, two 4-inch high-excursion fiber cone woofers and four passive bass radiators for maximum controlled low-end bass extension - all in an ultra-slim profile designed expressly for super-thin 65-inch or larger TVs.

Features

- **Low Frequency Driver**
 - Two 4" paper cone drivers with Two 4" paper cone passive radiators.
- **High Frequency Driver**
 - 1" x 1.4" Folded Motion Transducer with 5.25" x 1.75" diaphragm.
- **On-Wall or On-Shelf Versatility** - With keyhole slots on the speaker's back panel that attach easily to the included wall bracket, you'll have the SLM wall-mounted and playing in no time. While we created Motion SLM speakers to wall mount next to ultra-flat panel TVs, that's not their only application. Included* with each speaker is a curved black base to allow them to sit on a shelf or equipment cabinet (* SLM or SLM XL only).
- **The Audible Truth About Thin TVs** - TV manufacturers are pushing the physical limits of electronics, making TVs that are thinner than ever at less than 2-inches from the wall. While they look great, creating a thinner television means making compromises to the built-in speakers; tiny drivers, cheaper parts, reduced cabinet volume and placement behind the TV create unnatural, lifeless sound. Worse yet, these speakers are usually underpowered, and easily distort when you turn up the volume. Motion SLM speakers provides a clean, easy to install solution for elevating the aural experience that has been sacrificed with ultra-thin TV technology.
- **The Perfect LCR System** - Folded Motion tweeters have an 80° x 80° dispersion pattern, which allows SLM and SLM XL to sound exactly the same in a horizontal or vertical orientation, making them perfect for Left-Center-Right (LCR) system applications. The logo on the grille is magnetic and can move and rotate to the proper aesthetically pleasing location in any orientation. SLM and SLM XL both include a base designed for vertical applications, allowing the speakers sit on a shelf or equipment cabinet.
- **Slender Profile & Stunning Performance** - The secret to the Motion SLM's outstanding performance is the innovative dual 4-inch, ultra-slim fiber cone woofers and dual 4-inch high-velocity passive bass radiators, paired with a Folded Motion tweeter to create stunning acoustical alchemy typically found in much larger speaker systems. Hidden discretely underneath the grille, the drivers are held securely in place by a solid, black-anodized brushed aluminum baffle. The high-gloss black SLM cabinet is only 1.45-inches thin, for a total wall protrusion of 1.83-inches with magnetic grille and included wall mount bracket.

Frequency Response	100-25,000 Hz ±3dB
Recommended Amplifier Power	20-140 watts per channel
Horizontal Dispersion	80°

Vertical Dispersion	80°
Sensitivity	94 dB/2.83 volts/meter
Impedance	4 Ohms Compatible with 4, 6, or 8 Ohm rated amplifiers.
Crossover Frequency	3,100 Hz
High Frequency Transducer	1" x 1.4" (2.6cm x 3.6cm) Folded Motion Transducer with 5.25" x 1.75" (13.3cm x 4.4cm) diaphragm
Low Frequency Transducer	Two 4"(10.2cm) paper cone. Four 4"(10.2cm) paper cone passive radiators.
Components	Custom air core coil inductors. Polyester film capacitors in series and low DF electrolytic capacitors in parallel. Overall system thermal/current protection.
Inputs	Low-profile push style
Weight	9 lbs. (4.1 kg)
Dimensions	34.1" x 6.4" x 1.89 " (86.7cm x 16.2cm x 4.8cm)